

**NAME**

**scm** -- scm language

**DESCRIPTION**

The *scm* textual language was introduced in the Ph.D. thesis of Tristan Le Gall. An *scm* model contains the description of a system of communicating machines. This description is composed of two parts:

- A *header* that specifies the set of fifo channels and the message alphabet.
- A list of *automata*, each modeling a communicating machine.

For model-checking purposes, the format also permits the specification of a set of *bad configurations*.

**Header**

1. Start the description of a system of communicating machines and specify its name:

**scm** *ident* :

2. Specify the number of channels:

**nb\_channels** = *integer* ;

The set of channels is  $\{0, \dots, n-1\}$  where  $n$  is the number of channels. By default, all channels are perfect.

3. Tag some channels as lossy (optional):

[**lossy** : *integer* [, *integer* ...]]

4. Declare the message alphabet as follows:

**parameters** : [{**int** | **real**} *ident* [= *expr*] ; ...]

The alphabet is the same for all channels. Each message holds a typed numerical value.

**Automata**

1. Start the description of an automaton and specify its name:

**automaton** *ident* :

2. Declare the automaton's local variables (optional):

**[{int | real} ident [= expr] ; ...]**

3. Specify the automaton's initial states:

**initial : integer [, integer ...]**

4. Declare the automaton's states together with outgoing transitions:

**state integer : [to integer : command ; ...]**

where *command* is of the following form:

**when cond [, integer {! | ?} ident] [with ident = expr [, ident = expr ...]]**

### Semantics

The operational semantics of a system of communicating machines is the usual one: the automata move asynchronously according to their local transitions, and they communicate exclusively through the channels. Communication actions are ! (send) and ? (receive). Channels are fifo, unbounded, and initially empty. Note that channels need not be point-to-point, they are shared by all automata.

### Bad Configurations

The description of the system of communicating machines is, optionally, followed by the specification of a set of bad configurations:

**bad\_states : ( automaton ident : badlocal ... [with regexp] ) ...**

where *badlocal* is of the following form:

**in integer : cond ...**

The local constraints in a *badlocal* specification are *disjuncted* together. The *badlocal* specifications in a **bad\_states** declaration are *conjoined* together.

The queue contents are represented by a regular expression *regexp* as defined below.

### Regular Expressions

Queue contents for specifying bad states or displaying the current states of a system of communicating machines are represented by regular expressions of the following form:

*regexp*  
 ::= \_ | # | *a* for *a* in the message alphabet  
 | *regexp* . *regexp* | ( *regexp* | *regexp* )  
 | *regexp* ^\* | *regexp* ^+

The operators on regular expressions are interpreted as usually:  $.$  stands for concatenation,  $|$  for disjunction,  $^*$  is the reflexive-transitive closure, and  $^+$  the transitive closure. The empty word is denoted by  $_$ .

The symbol  $\#$  is interpreted as separator for channels in *regex*. Each word matched by *regex* must contain exactly  $n-1$  occurrences of  $\#$  where  $n$  is the number of channels.

### EXAMPLE

The following example is the classical connection/disconnection protocol.

```
scm connection_disconnection :
nb_channels = 2 ;
parameters :
  real o ;
  real c ;
  real d ;
automaton sender :
  initial : 0
  state 0 :
    to 1 : when true , 0 ! o ;
  state 1 :
    to 0 : when true , 0 ! c ;
    to 0 : when true , 1 ? d ;
automaton receiver :
  initial : 0
  state 0 :
    to 1 : when true , 0 ? o ;
  state 1 :
    to 0 : when true , 0 ? c ;
    to 0 : when true , 1 ! d ;
bad_states:
  (automaton receiver: in 0 : true with c.(o|c)^*.#.d^*)
```

This *scm* model has two channels, with message alphabet  $\{o, c, d\}$ . There are two automata, a sender and a receiver. Their states and transitions should be self-explanatory. Bad configurations are those where (a) the receiver is in local state 0, and (b) channel contents are in the regular expression detailed below.

The regular expression  $c.(o|c)^*.\#.d^*$  is interpreted as the set of contents of two channels:

- The first containing any word over the alphabet  $\{o, c\}$  that starts with a message  $c$ .
- The second containing an arbitrary sequence of  $d$  (which can be of zero length, i.e., empty).

**SEE ALSO**

control(1), verify(1)